



IMB - International Machines à Bois

1351 chemin de la paix, Zi Balauques 84350 Courthézon

04 90 70 50 33 / 06 19 61 55 98

j.morsi@imb-machines.com et n.leuci@imb-machines.com

www.international-machines-bois.com

Flat saw Biesse Selco EB80

Biesse - EB80



Technical description

Flat saw Selco EB80

MAIN TECHNICAL FEATURES

Maximum cutting length: 3800mm

Maximum stroke of the pusher: 3200mm.

Max. machine size (width x length): 6585 x 6026mm.

Max overrun of the blade in relation to the work surface: 80mm.

Max opening panel locking clamps: 80mm.

Worktop height: 935 ± 15mm.

STANDARD CONFIGURATION INCLUDING:

Main blade motor 11 kW / 50 Hz (14.7 HP)

Blade motor - 2.2 kW / 50 Hz (3 HP)

Automatic blade overrun control

Quick and safe blade change in the square area on the front side

Manual adjustment of the scorer from the top of the blade change housing

Blade-scoring exclusion directly from the console, by means of a pusher



IMB - International Machines à Bois

1351 chemin de la paix, Zi Balauques 84350 Courthézon

04 90 70 50 33 / 06 19 61 55 98

j.morsi@imb-machines.com et n.leuci@imb-machines.com

www.international-machines-bois.com

Flat saw Biesse Selco EB80

Biesse - EB80

Technical description (continuation)

Brushless motor for moving the blade carriage - speed 1 - 100 m / min

Pusher shaft with Brushless motor - max speed 60 m / min.

Lateral alignment device with automatic intervention and pre-positioning with a roller (min. 60 mm. - max. 2200 mm.)

Safety devices according to the standards in force